

18-2019



EXPERIENCE COLD QUALITY

cooldura.
experience cold quality



LED light inside doorframe

C4L-I LED DOOR - BOTTLE COOLER

Product features:

- Fan assisted cooling
- LED light inside door frame
- Glass door
- 4 adjustable shelves
- Adjustable feet

TECHNICAL DATA

Climate Class	4
Temperature Range, °C	2 to 10
Gross Volume, l.	372
Net. Volume, l.	347
External Dimensions, WxDxH	595x640x1840
Internal Dimensions, WxDxH	470x440x1555
Packing Dimensions, WxDxH	680x710x1940
40'ft Container load, pcs.	54
Door	1 hinged glass
Shelves	4, 490x360
Exterior	White
Interior	ABS
Castors/Feet	2 rollers and 2 adjustable feet
Lock	Yes
Voltage/Frequency, V/Hz.	220-240/50
Rated Input Power, W.	295
Energy Consumption. kWh/24h.	1.6
Gross Weight, kg.	80
Net. Weight, kg.	72
Noise Level, db(A)	45
Type of Cooling	Fan assisted
Type of Defrost	Automatic
Type of Control	Mechanical
Thermometer	Yes
Refrigerant	R600a
Charge, g.	80
Internal Light	LED inside door frame



LED light inside doorframe

C4C-I 2LED DOOR - BOTTLE COOLER

Product features:

- Illuminated canopy
- Fan assisted cooling
- LED light inside door frame
- 4 adjustable shelves
- Adjustable feet

TECHNICAL DATA

Climate Class	4
Temperature Range, °C	2 to 10
Gross Volume, l.	372
Net. Volume, l.	347
External Dimensions, WxDxH	595x640x1980
Internal Dimensions, WxDxH	470x440x1555
Packing Dimensions, WxDxH	680x710x2080
40'ft Container load, pcs.	54
Door	1 hinged glass
Shelves	4, 490x360
Exterior	White
Interior	ABS
Castors/Feet	2 rollers and 2 adjustable feet
Lock	Yes
Voltage/Frequency, V/Hz.	220-240/50
Rated Input Power, W.	295
Energy Consumption. kWh/24h.	1.66
Gross Weight, kg.	83
Net. Weight, kg.	75
Noise Level, db(A)	45
Type of Cooling	Fan assisted
Type of Defrost	Automatic
Type of Control	Mechanical
Thermometer	Yes
Refrigerant	R600a
Charge, g.	80
Internal Light	LED inside door frame
Canopy light 15	W Neon



S10-I - BOTTLE COOLER

Product features:

- Fan assisted cooling
- Interior LED light
- Reversible glass door
- 4 adjustable shelves
- Adjustable feet

TECHNICAL DATA

Climate Class	4
Temperature Range, °C	2 to 10
Gross Volume, l.	290
Net. Volume, l.	260
External Dimensions, WxDxH	595x640x1635
Internal Dimensions, WxDxH	470x440x1347
Packing Dimensions, WxDxH	680x710x1740
40'ft Container load, pcs.	54
Door	1 hinged glass
Shelves	4, 490x360
Exterior	White
Interior	ABS
Castors/Feet	2 rollers and 2 adjustable feet
Lock	Yes
Voltage/Frequency, V/Hz.	220-240/50
Rated Input Power, W.	266
Energy Consumption. kWh/24h.	2
Gross Weight, kg.	78
Net. Weight, kg.	70
Noise Level, db(A)	45
Type of Cooling	Fan assisted
Type of Defrost	Automatic
Type of Control	Mechanical
Thermometer	Yes
Refrigerant	R600a
Charge, g.	70
Internal Light	LED



S15-I - BOTTLE COOLER

Product features:

- Fan assisted cooling
- Interior LED light
- Reversible glass door
- 5 adjustable shelves
- Adjustable feet

TECHNICAL DATA

Climate Class	4
Temperature Range, °C	2 to 10
Gross Volume, l.	372
Net. Volume, l.	347
External Dimensions, WxDxH	595x640x1840
Internal Dimensions, WxDxH	470x440x1555
Packing Dimensions, WxDxH	680x710x1940
40'ft Container load, pcs.	54
Door	1 hinged glass
Shelves	5, 490x360
Exterior	White
Interior	ABS
Castors/Feet	2 rollers and 2 adjustable feet
Lock	Yes
Voltage/Frequency, V/Hz.	220-240/50
Rated Input Power, W.	295
Energy Consumption. kWh/24h.	2.3
Gross Weight, kg.	85
Net. Weight, kg.	77
Noise Level, db(A)	45
Type of Cooling	Fan assisted
Type of Defrost	Automatic
Type of Control	Mechanical
Thermometer	Yes
Refrigerant	R600a
Charge, g.	80
Internal Light	LED



TROLLEY

External dimensions, WxDxH: 695x695x1495mm

Internal dimensions, WxDxH: 645x645x1445mm

Trolley is equipped with quality wheels, diameter 100mm.

Combination trolley with refrigerator makes the external dimensions of the coolers always 150mm higher.

cooldura.
experience cold quality

+31 (0)85 043 5840

info@cooldura.com

www.cooldura.com